

Series Table (產品一覽表)

Series Features (特點)		Temp (°C)	Voltage (VDC)	Cap. (μF)	Load Life	Appearance	Page
Radial Led Type							引線式
ULG	+105°C, High Ripple Current, Super Low ESR (高紋波, 超低阻抗)	-55 ~ +105°C	2.5 to 35	22 to 1500	2000 hours	Sleeveless Low ESR	P.13
ULR	+105°C, Higher Ripple Current, Lower ESR Than ULG (高紋波, 比ULG更低阻抗)	-55 ~ +105°C	2.5 to 35	22 to 2700	2000 hours	Sleeveless Lower ESR	P.15
NEW UER	+105°C, Higher Ripple Current, Long Life 5000 Hours (高紋波, 長壽命)	-55 ~ +105°C	2.5 to 16	100 to 1200	5000 hours	Sleeveless Lower ESR	P.19
USR	+105°C, Higher Ripple Current, Lower ESR Than ULG (高紋波, 比ULG更低阻抗)	-55 ~ +105°C	2.5 to 16	100 to 2700	2000 hours	Sleeved Lower ESR	P.21
V-Chip Type							貼片式
UVG	+105°C, Surface Mount Type, General Purpose (貼片標準品)	-55 ~ +105°C	2.5 to 25	22 to 820	2000 hours	V-chip	P.24
UVR	+105°C, Surface Mount Type, Lower ESR Than UVG (貼片標準品, 比UVG更低阻抗)	-55 ~ +105°C	2.5 to 16	100 to 1000	2000 hours	V-chip Low ESR	P.26

Series Chart (產品體系圖)

